



Bioelectrochemical systems serve anaerobic digestion process for process monitoring and biogas upgrading

Jin, Xiangdan; Angelidaki, Irini; Zhang, Yifeng

Publication date:
2018

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):
Jin, X., Angelidaki, I., & Zhang, Y. (2018). *Bioelectrochemical systems serve anaerobic digestion process for process monitoring and biogas upgrading*. Abstract from 4th EU-ISMET 2018, Tyne, United Kingdom.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



Bioelectrochemical systems serve anaerobic digestion process for process monitoring and biogas upgrading

Xiangdan Jin, Irini Angelidaki, Yifeng Zhang

Department of Environmental Engineering, Technical University of Denmark, DK-2800 Kongens Lyngby, Denmark

yifz@env.dtu.dk

Bioelectrochemical systems (BESs), which employ microbes as catalysts to convert chemical energy stored in organic matter into sustainable electricity and high-value chemicals, is an emerging and promising technology. BESs have broad applications including wastewater treatment, chemical production, resource recovery and waste remediation. Recently, new concepts of integrating BES with anaerobic digestion (AD) for process optimization have been proposed. The purpose of this work was to optimize the AD process using BES in two aspects: developing a new volatile fatty acid (VFA) monitoring system which can be used as the AD process indicator, and for improving biogas quality by removing CO₂. Firstly, a microbial desalination cell (MDC) was developed for measuring VFAs concentrations during AD process. The response time was approx. 5 h and the detection range was 1 to 200 mM. Secondly, in order to reduce the construction cost and response time, microbial electrolysis cell (MEC) was employed as VFA biosensor. The response of the biosensor was only 1 h due to the faster transfer of VFAs supported by the external voltage. The produced H₂ could potentially contribute to the energy needs for operating the biosensor and thereby to a self-sustaining system. Thirdly, to improve biogas quality, a microbial electrolytic capture, separation and regeneration cell (MESC) was developed. In MESC, acid and alkaline generation, CO₂ capture, biogas upgrading and wastewater treatment were simultaneously achieved.