Oxide Thin-Films for Protection and Functionalization of Photocathodes in Tandem Water-Splitting Devices

Vesborg, Peter Christian Kjærgaard; Seger, Brian; Chorkendorff, Ib; Hansen, Ole

Published in:
Electrochemical Society. Meeting Abstracts (Online)

Publication date:
2013

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Vesborg, P. C. K., Seger, B., Chorkendorff, I., & Hansen, O. (2013). Oxide Thin-Films for Protection and Functionalization of Photocathodes in Tandem Water-Splitting Devices. *Electrochemical Society. Meeting Abstracts (Online)*.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Oxide thin-films for protection and functionalization of photocathodes in tandem water-splitting devices.

Peter C. K. Vesborg, Brian Seger, Ib Chorkendorff, Ole Hansen

Many light-harvesting semiconductors with good optical and electronic properties cannot be directly used in PEC water-splitting systems due to poor stability under working conditions. In recent years there has been a large interest in protecting sensitive absorber materials such as silicon or Cu₂O [1-3] with thin films of highly stable oxides such as TiO₂ and similar materials.

We show that such oxides can be deposited so that they provide month-long stability under continuous PEC operation on sensitive absorbers in corrosive electrolytes. We also show, that since electrons may transport through such oxides via the conduction band, they can be made thick (> 100 nm) and thus very durable without causing problematic voltage loss. Finally we show that the oxides may serve a double purpose of simultaneously providing corrosion protection and screening the semiconductor from the electrolyte while setting up a space-charge region in the underlying semiconductor to facilitate electron-hole separation paving the way for high open-circuit voltage photoelectrodes.

REF:

[1]

Hydrogen Production Using a Molybdenum Sulfide Catalyst on a Titanium-Protected n+p-Silicon Photocathode,
Brian Seger, Anders B. Laursen, Peter C. K. Vesborg, Thomas Pedersen, Ole Hansen, Søren Dahl, Ib Chorkendorff,
Angewandte Chemie International Edition, Volume 51, Issue 36, pages 9128–9131, September 3, 2012, DOI: 10.1002/anie.201203585

[2]

Using TiO₂ as a Conductive Protective Layer for Photocathodic H₂ Evolution,
Brian Seger, Thomas Pedersen, Anders B. Laursen, Peter C. K. Vesborg, Ole Hansen, and Ib Chorkendorff
J. Am. Chem. Soc., 2013, 135 (3), pp 1057–1064
DOI: 10.1021/ja309523t

[3]

Highly active oxide photocathode for photoelectrochemical water reduction,
Adriana Paracchino, Vincent Laporte, Kevin Sivula, Michael Grätzel and Elijah Thimsen
Nature Materials 10, 456–461 (2011) doi:10.1038/nmat3017