Ni based solid oxide cell electrodes

Mogensen, Mogens Bjerg; Holtappels, Peter

Published in:
Proceedings

Publication date:
2010

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Mogensen, M. B., & Holtappels, P. (2010). Ni based solid oxide cell electrodes. In P. Connor (Ed.), *Proceedings European Fuel Cell Forum*.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Ni based solid oxide cell electrodes

Mogens Mogensen, Peter Holtappels

Fuel Cells and Solid State Chemistry Division

Risø National Laboratory for Sustainable Energy, The technical University of Denmark

DK-4000 Roskilde, Denmark

Tel.: +45-46775726, Fax: +45-46775858

momo@risoe.dtu.dk

Abstract

The Ni-cermet with either yttria stabilised zirconia (YSZ) or doped ceria has so far been the unbeatable anode in SOFCs in spite of the many problems associated with this electrode. The main reason for this is the excellent catalytic and electrocatalytic property of Ni for steam reforming of natural gas and for electrochemical oxidation of H_2 and CO. These properties have been so good that they have overshadowed several drawbacks such as the sensitivity to sulphur poisoning and mechanical instability in case of redoxing. Furthermore, the electrode is fully reversible, i.e. works equally well in fuel cell and in electrolysis mode.

This paper is a critical review of the literature of nickel based electrodes for application in solid oxide cells at temperature from 500 – 1000 °C. The applications may be fuel cells or electrolyser cells. The reviewed literature is that of experimental results on both model electrodes and practical composite cermet electrodes. A substantially longer three-phase-boundary (TPB) can be obtained per unit area of cell in such a composite of nickel and electrolyte material, provided that two interwoven solid networks of the two phases are obtained to provide a three dimensional TPB throughout the electrode volume.

Variables that are used for controlling the properties of Ni-cermet-electrodes are: 1) Ni/YSZ volume ratio, and 2) porosity and particle size distribution which is mainly affected by raw materials morphology, application methods and production parameters such as milling and sintering possible followed by infiltration of nano sized electrocatalytic active particles. The various electrode properties are deeply related to these parameters, but also much related to the atomic scale structure of the Ni-electrolyte interface, which in turn is affected by segregation of electrolyte components and impurities as well as poisons in the gas phase.

Main emphasis will be put on the following subjects: a) electronic conductivity of cermets, b) dimensional and thermodynamic stability including redoxing, c) thermal expansion coefficient matching, e) chemical compatibility with stack components and gaseous reactants, f) sensitivity towards impurities in the fuel, and g) electrode reaction mechanism and polarisation resistance including the reports on model electrodes. Data on relations between cermet structure and polarisation resistance will be presented and discussed.

A brief discussion of main concepts in the modelling literature will be given in context of the latter subject.