



Development of a pressure based room acoustic model using impedance descriptions of surfaces

Marbjerg, Gerd; Brunskog, Jonas; Jeong, Cheol-Ho; Nilsson, Erling

Published in:
Proceedings of Internoise 2013

Publication date:
2013

[Link back to DTU Orbit](#)

Citation (APA):
Marbjerg, G. H., Brunskog, J., Jeong, C-H., & Nilsson, E. (2013). Development of a pressure based room acoustic model using impedance descriptions of surfaces. In Proceedings of Internoise 2013

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

inter noise

2013 | INNSBRUCK | AUSTRIA

15.-18. SEPTEMBER 2013

NOISE CONTROL FOR QUALITY OF LIFE

Development of a pressure based room acoustic model using impedance descriptions of surfaces

Gerd Marbjerg¹, Jonas Brunskog², Cheol-Ho Jeong³ and Erling Nilsson⁴

¹ Saint-Gobain Ecophon, 2650 Hvidovre, Denmark

^{1,2,3} Acoustic Technology, Technical University of Denmark, 2800 Kongens Lyngby, Denmark

⁴ Saint-Gobain Ecophon, 265 03 Hyllinge, Sweden

ABSTRACT

If a simulation tool is to be used for the optimization of absorbent ceilings, it is important that the simulation tool includes a good description of the surface. This study therefore aims at developing a model which can describe surfaces by their impedance values and not just by their statistical absorption coefficient, thus retaining the phase and the angle dependence. The approach of the proposed model will be to calculate the pressure impulse response using a combination of the image source method and acoustic radiosity. The image source method will account for the specular reflections and acoustic radiosity will account for the diffuse reflections.

This paper presents the motivation for the new model in the form of results in literature, which show the importance of retaining the angle dependence and phase information in reflections along with simple examples of angle dependent reflection from a porous absorber.

Keywords: Room acoustics, computer modelling

1. INTRODUCTION

In many models used for room acoustic simulations very simple descriptions of the surface properties are used. For some room configurations these simplified descriptions are not suitable, and in some cases these simplifications cause great errors in the prediction of the sound field. A widely used description of surface properties is the statistical absorption coefficient combined with scattering coefficients. The statistical absorption coefficient only expresses how large a fraction of energy incident on a surface is reflected independently of the angle at which the sound hits the surface and thereby disregards any angle dependence of the absorption and phase shifts in the reflection. Especially if the purpose of the room simulations is to optimise the properties of the surfaces then the surface properties should be carefully controlled and thoroughly described. In the present model it is therefore proposed to use an impedance description of the surfaces, which can account for both the angle dependence and the phase shift upon reflection.

¹ ghmar@elektro.dtu.dk

² jbr@elektro.dtu.dk

³ chj@elektro.dtu.dk

⁴ erling.nilsson@ecophon.se