



## Water transport in graphene nano-channels

Wagemann, Enrique; Oyarzua, Elton; Walther, J. H.

*Publication date:*  
2015

*Document Version*  
Peer reviewed version

[Link back to DTU Orbit](#)

*Citation (APA):*

Wagemann, E., Oyarzua, E., & Walther, J. H. (2015). Water transport in graphene nano-channels. Abstract from 68th Annual Meeting of the American Physical Society's Division of Fluid Dynamics (DFD) , Boston, United States.

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Abstract Submitted  
for the DFD15 Meeting of  
The American Physical Society

**Water transport in graphene nano-channels<sup>1</sup>** ENRIQUE WAGEMANN, ELTON OYARZUA, University of Concepcion, J. H. WALTHER, Technical University of Denmark, HARVEY ZAMBRANO, University of Concepcion — The transport of water in nanopores is of both fundamental and practical interest. Graphene Channels (GCs) are potential building blocks for nanofluidic devices due to their molecularly smooth walls and exceptional mechanical properties. Numerous studies have found a significant flow rate enhancement, defined as the ratio of the computed flow rate to that predicted from the classical Poiseuille model. Moreover, these studies point to the fact that the flow enhancement is a function of channel height and the fluid-wall physical-chemistry. In spite of the intensive research, an explicit relation between the chirality of the graphene walls and the slip length has not been established. In this study, we perform non-equilibrium molecular dynamics simulations of water flow in single- and multi-walled GCs. We examine the influence on the flow rates of dissipating the viscous heat produced by connecting the thermostat to the water molecules, the CNT wall atoms or both of them. From the atomic trajectories, we compute the fluid flow rates in GCs with zig-zag and armchair walls, heights from 1 to 4 nm and different number of graphene layers on the walls. A relation between the chirality, slip length, and flow enhancement is found.

<sup>1</sup>We acknowledge partial support from Fondecyt project 11130559 and Redoc udec.

Enrique Wagemann  
University of Concepcion

Date submitted: 31 Jul 2015

Electronic form version 1.4