



Incorporation of treated straw and wood fly ash into clay building brick

Chen, Wan; Ottosen, Lisbeth M.; Jensen, Pernille Erland; Kirkelund, Gunvor Marie

Published in:

International RILEM Conference on Materials, Systems and Structures in Civil Engineering

Publication date:

2016

Document Version

Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Chen, W., Ottosen, L. M., Jensen, P. E., & Kirkelund, G. M. (2016). Incorporation of treated straw and wood fly ash into clay building brick. In *International RILEM Conference on Materials, Systems and Structures in Civil Engineering: Conference segment on Electrochemistry in Civil Engineering* (pp. 151-151). Rilem publications.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

INCORPORATION OF TREATED STRAW AND WOOD FLY ASH INTO CLAY BUILDING BRICK

Wan Chen ⁽¹⁾, **Lisbeth M. Ottosen** ⁽¹⁾, **Pernille E. Jensen** ⁽¹⁾, **Gunvor M. Kirkelund** ⁽¹⁾

(1) Department of Civil Engineering, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark

Abstract

High Cd content in straw and wood fly ash, generated from biomass-fired power plants, prohibits its recycling as fertilizer spreading on the landfilled. To improve and alter the current mainstream of fly ash treatment by landfilling, different approaches were tried for treatment of straw and wood fly ash, such as washing with water to quickly recover the highly soluble salts (mainly K and Cl), and treatment of the washed fly ash with elevated heavy metal content resulted from washing by electro-dialytic remediation (EDR).

The finding that SiO₂ (quartz) accounted for a significant portion in the treated ash, suggests the possibility of the ash reuse in sintered clay bricks. In this study, the straw and wood fly ash treated by washing and EDR was incorporated into yellow clay bricks at different substitution rates. The properties of the clay-ash bricks were studied in terms of shrinkage, water absorption, porosity, density, compressive strength and leaching behavior, and compared with the 100% clay bricks. It's promising to use the treated ash as a secondary building material.