



Effect of supercritical extraction on the soot nanostructure and gasification product yields

Trubetskaya, Anna; Kling, Jens; Umeki, Kentaro ; Attard, Thomas M. ; Budarin, Vitaliy L.

Publication date:
2018

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):

Trubetskaya, A., Kling, J., Umeki, K., Attard, T. M., & Budarin, V. L. (2018). Effect of supercritical extraction on the soot nanostructure and gasification product yields. Poster session presented at 37th International Symposium on Combustion, Dublin, Ireland.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.




Anna Trubetskaya^{1*}, Jens Kling², Kentaro Umeki³, Thomas M. Attard⁴, Vitaliy L. Budarin⁴ and Andrew J. Hunt⁵

¹Mechanical Engineering Department, National University of Ireland Galway, H91 TK33, Galway, Ireland
²Center for Nanoscopy, Technical University of Denmark, 2800 Kgs. Lyngby, Denmark
³Energy Science Division, Luleå University of Technology, 97187, Luleå, Sweden
⁴Department of Chemistry, The University of York, Heslington, York, YO10 5DD, United Kingdom
⁵Department of Chemistry, Khon Kaen University, 123 Mittrapharb Road, 40002, Khon Kaen, Thailand


*anna.trubetskaya@nuigalway.ie

Introduction: The cost-efficient development of biorefinery depends on feedstock flexibility and combination of pre-treatment processes with the power and heat generation [1]. The pre-treatment processes decrease the water content in feedstock, increase energy density, and bring the high value-added products to the chemical and liquid fuel industries, whereas the remaining solid fuel fractions are used for the renewable and clean energy generation. Supercritical carbon dioxide extraction significantly reduces the risks associated with off-gassing and oxygen depletion during fuel storage [2], while the extracted fatty acids can be utilized as a primary feedstock for chemicals and biorefinery applications [3,4]. In addition, the high content of extractives in softwood might create challenges with fuel feeding and conversion during gasification. Forest industry produces millions of tons of waste wood residues which can be used in a closed loop efficient process. The supercritical extraction and biomass microwave pyrolysis have a high potential to remove extractives and other volatile compounds, and thus, to reduce the formation of solid residues in the entrained flow gasification.


Closed loop biorefinery process




Methodology: Original and supercritical CO₂ extracted needles and branches were pyrolyzed at 1100°C in the drop tube reactor (DTF). The results were compared with scCO₂ extracted branches which were firstly treated in a microwave reactor and subsequently reacted in the DTF under pyrolysis and CO₂ gasification conditions.



Soot from original needles



Soot from scCO₂ extracted needles



Conclusion and Future studies: The results showed that biomass pre-treatment using supercritical CO₂ extraction is a promising way to decrease char yield in high temperature processes with the concomitant production of an added-value feedstock in the green chemical and energy industry. Optimized supercritical extraction conditions allowed to extract more than half of fatty and resin acid compounds from pine needles and branches. Supercritical extraction had no influence on the soot yield, whereas the differences in nanostructure of soot from original needles and branches and samples after scCO₂ were obvious. Soot particles from original wood fraction were irregular-shaped with the longer graphene segments (13.2 nm) and lower curvature compared to soot particles from scCO₂ extracted wood fractions which obtained a structure similar to soot from low ash-containing stemwood. The additional heat treatment of char from microwave pyrolysis led to the low soot yield and high syngas formation under pyrolysis and CO₂ gasification conditions. Microwave pyrolysis of scCO₂ treated branches has potential to produce liquid products for the chemicals and fuels, whereas the remaining char can be used as a feedstock in high temperature processes. Future studies are planned to scale up supercritical CO₂ extraction, microwave pyrolysis and entrained flow gasification to the industrial pilot plant.

References

- [1] T.M. Attard, N. Bukhanko, D. Eriksson, M. Arshadi, P. Geladi, U. Bergsten and etc., *Supercritical extraction of waxes and lipids from biomass: A valuable first step towards an integrated biorefinery*, J. Cleaner Product. **177**, 684-98 (2018).
- [2] T.M. Attard, M. Arshadi, C. Nielsson, V.L. Budarin, E. Valencia-Reyes, J.H. Clark and etc., *Impact of supercritical extraction on solid fuel wood pellet properties and off-gassing during storage*, Green Chem. **18**(9), 2682-90 (2016).
- [3] K. Hill, *Fats and oils as oleochemical raw materials*, Pure Appl. Chem. **72**(7), 1255-64 (2000).
- [4] N.A. Ruston, *Commercial uses of fatty acids*, J. Am. Oil Chem. Soc. **29**(11), 495-8 (1952).
- [5] A. Trubetskaya, G.R. Surup, T.M. Attard, V.L. Budarin, A.J. Hunt, K. Umeki and etc., *High-temperature treatment of char-derived from microwave pyrolysis and supercritical solvent extracted wood fractions*, Renew. Energy submitted (2018).

